


ESS-215-258KLA-SA1

Energy storage cabinet



Efficient & Flexible

- Modular design, flexible expansion
- Intelligent liquid cooling control, reducing auxiliary power loss
- Low-noise operation



Safety & Friendly

- Electrical cables and liquid pipes separated design
- Cell-level / PACK-level / cabin-level fire extinguishing
- Front exhaust, top explosion venting
- IP55 protection, C4 corrosion resistance, strong environmental adaptability



Smart management

- Integrated EMS functions: anti-backflow, parallel power distribution, demand management, peak shaving and valley filling, self-consumption
- Supports remote operation and maintenance

www.sofarsolar.com

© As of November 2025, SOFARSOLAR Co.,Ltd. The depiction of colors and shape of the product may differ from the original. SOFAR reserves the right to make changes or improvements to the products without prior notice. Ordering information is valid for specialist retailers. All brands or logos are trademarks or registered trademarks of their respective owners. All rights, technical modifications, and errors reserved.

Model	ESS-258KLA-SA1	ESS-215KLA-SA1
DC Side		
Battery Type	LFP/280Ah	
Rated Energy	258 kWh (6Pack)	215 kWh (5Pack)
Rated Voltage	921.6V	768V
DC Operating Voltage Range	734.4V ~ 1036.8V DC	612 V ~ 864V DC
Recommend DC Voltage Range	777.6V ~ 1022.4V DC	648 V ~ 852V DC
AC Side		
AC Voltage	400V AC	
Rated Power	125 kW	
Maximum AC Power	138 kW	
Maximum AC Current	198A	
Rated Grid Frequency	50Hz/60Hz	
Power Factor	-1~1	
System Parameters		
Operating Ambient Temperature	-30°C-50°C (Derating above 45°C)	
Storage Ambient Temperature	-30°C-60°C	
Operating Relative Humidity	0~100% (No condensation)	
Cooling Type	Liquid cooling	
Fire Suppression	1. Battery cell level (perfluorohexanone) 2. Canibet level (perfluorohexanone or aerosol) 3. Water fire suppression	
System Configuration	AC side: Maximum 6 Energy storage cabinets in parallel DC side: Maximum 3 Battery cabinets per Energy storage cabinet	
Grid-On/Off	Auto-switch (With backup cabinet)	
Cabinet Connection	Plug-in connector	
Dimension (W×D×H)	1450×1350×2200 mm	
Weight	< 2.8T	< 2.5T
Ingress Protection Rating	IP55	
Anti-corrosion	C4 (C5 optional)	
Operating Altitude	≤ 4000m (Derating above 2000m)	
Noise Level	≤ 60dB	
Installation	Ground mounting	
Communication interface	Ethernet, Dry connect	
Standard	IEC/EN 61000-6-2/4, IEC62477-1, IEC62619, UN38.3, UL9540A, UL1973	

*All specifications are subject to change without notice.